

LED Followspot 75ST

HIGHLIGHTS

- Portable, LED followspot emits a focused beam with a sharp edge
- Set up and tear down in seconds with the included tripod
- Increase flexibility with DMX and manual control options
- A great option for small clubs and auditoriums
- Simplify professional fading with smooth LED dimming
- Deliver silent operation with fast electronic strobe and no moving parts
- Project crisp patterns onto any surface using the single gobo slot
- Focus the light where it is needed using the mechanical iris to reduce the beam's diameter

SPECIFICATIONS

- DMX Channels : 3
- DMX Connectors : 3-pin XLR
- Colors : 7 + white
- Light Source : 1 LED (cool white) 75 W (18 A) 50,000 hours life expectancy
- Strobe Rate : 0 to 16 Hz
- Illuminance : 8,140 lux @ 2 m (14°)
4,650 lux @ 2 m (20°)
- Input Voltage : 120/230 VAC, 50/60 Hz (switchable)
- Power and Current : 215 W, 1.8 A @ 120 V, 60 Hz
220 W, 1 A @ 230 V, 50 Hz
- Gobo Size : 23.7 mm outside, 21.3 mm image, 1 mm max thickness
- Zoom Angle : 14° to 20° (manual)
- Weight : 13.3 lb (6 kg)
- Dimensions : 22 x 10.8 x 11.5 in (560 x 276 x 292 mm)
- Approvals : CE, MET
- Stand Height : 2.8 to 3.8 ft (0.8 to 1.2) m

WHAT'S INCLUDED

- Power cord
- Tripod
- Warranty card

