

LFS-5D

HIGHLIGHTS

- Compact, LED framing spot shines a hard-edged beam perfect for gobo projection
- Fade the LED by connecting to a dimmable circuit such as the DMX-4 LED
- Highlight areas by altering the projected beam with framing shutters
- Easily print your own gobos on transparency film
- Flexibility to project from any distance using the 16° to 24° zoom range
- Includes four popular gobos to complement a variety of events
- Save time running cables and extension cords by power linking multiple units
- Easily transports in the CHS-40 VIP Gear Bag

SPECIFICATIONS

- Gobos : 25.4 mm outside, 19 mm image, 1 mm max thickness (size V)
- Light Source : 1 LED (white) 23 W (15.3 A), 50,000 hours life expectancy
- Illuminance : (16°): 2,300 lux @ 2 m
(24°): 1,050 lux @ 2 m
- Power Linking : 23 units @ 120 V; 45 units @ 230 V
- Input Voltage : 120 VAC, 60 Hz or 230 V, 50 Hz
- Power and Current : 52 W, 0.4 A @ 120 V, 60 Hz
56 W, 0.2 A @ 230 V, 50 Hz
- Zoom Angle : (manual): 16° to 24°
- Weight : 3.2 lb (1.5 kg)
- Size : 12.5 x 7.5 x 9.5 in (318 x 191 x 241 mm)
- Approvals : CE

