

LFS-75DMX

HIGHLIGHTS

- 75-W LED framing spot shines a hard-edged, white spot in any direction
- Choose from 8 vivid colors via the automated color wheel
- Increase design options with built-in dimmer, DMX control and color wheel
- Accepts both round and square gobos to make setup easier
- Internal thermostat monitors temperatures to control fan speed
- Eliminate the need for DMX control with advanced standalone operation
- Easily highlight areas by altering the projected beam with framing shutters
- Flexibility to project from any distance using the 14° to 22° zoom range
- Includes four popular gobos and a gel frame holder
- Save time running extension cords by power linking multiple units
- Easily transports in the CHS-50 VIP Gear Bag



SPECIFICATIONS

- DMX Channels : 4
- DMX Connectors : 3- and 5-pin XLR
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Light Source : 1 LED (white) 75 W (16.9 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Illuminance : (14°): 8,710 lux @ 2 m
(22°): 3,660 lux @ 2 m
- Power Linking : 8 units @ 120 V; 14 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 117 W, 1.6 A @ 120 V, 60 Hz
115 W, 0.9 A @ 230 V, 50 Hz
- Gobo Size : 40 mm outside, 18 mm image, 1 mm max thickness
- Zoom Angle : (manual): 14° to 22°
- Weight : 8 lb (3.7 kg)
- Size : 15.1 x 11.1 x 13.6 in (385 x 283 x 345 mm)
- Approvals : CE

WHAT'S INCLUDED

- 75W LED
- 8 Automated Color Wheel
- Gobo & Gel Frame Holder