

Pinspot Bar

HIGHLIGHTS

- High-output bar with 6 independent pinspots designed to replicate traditional incandescent lamps
- No messy cables ensure a clean and elegant look for any upscale event
- Independent control of each head offers true flexibility and programming capabilities
- Includes various beam diffusers and 2700 K filters to help achieve the desired look
- Control via the on-board digital display, DMX, a wireless IRC-6 remote or D-Fi USB dongle
- A pair of included Omega brackets allow for multiple mounting options including pipe and drape
- PowerCon compatible power input and power linking saves time running cables
- Flicker-free operation suitable for on-camera use

SPECIFICATIONS

- DMX Channels : 1, 6 and 11
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 6 LEDs (warm white) 15 W, (3.6 A), 50,000 hours life expectancy
- PWM Frequency : 1000 Hz
- Beam Angle : 5°
- Field Angle : 11°
- Illuminance : 7,707 lux @ 2 m (per pod)
- Power Linking : 8 units @ 120 V; 13 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 171 W, 1.4 A @ 120 V, 60 Hz
191 W, 0.8 A @ 230 V, 50 Hz
- Weight : 9.4 lb (4.3 kg)
- Size : 39 x 4.6 x 5 in (1000 x 119 x 131 mm)
- Approvals : CE, RoHS
- Color Temperature : 4000 K
- CRI : 81
- Bracket Mounting Hole : 13 mm
- Optional Controllers : IRC-6, D-Fi USB

WHAT'S INCLUDED

- Pinspot Bar
- Power cord
- 2 Omega Brackets
- 6 10° diffusers
- 6 20° diffusers
- 6 2700 K CTO filters
- Quick Reference Guide

