

Shocker Panel 180 USB

HIGHLIGHTS

- High-power, LED strobe light creates attractive effects using 4 zones of control
- Rugged die-cast housing makes it ideal for mobile applications
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Trigger eye-catching effects with built-in automated programs via Master/Slave, DMX mode or optional IRC-6 remote
- Multiple programs create pulsing effects and chases
- Combine zone control and special effect macros for stunning visual impact
- Save time running cables and extension cords by power linking multiple units
- Easily transports in the optional CHS-25 VIP Gear Bag



SPECIFICATIONS

- DMX Channels : 2, 5 or 8
- DMX Connectors : 3-pin XLR
- Light Source : 180 SMD LEDs (cool white) 0.5 W (644 mA), 50,000 hours life expectancy
- Strobe Rate : 0 to 29 Hz
- Beam Angle : 65°
- Illuminance : 257 lux @ 2 m
- Power Linking : 13 units @ 120 V; 24 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 41 W, 0.6 A @ 120 V, 60 Hz
40 W, 0.3 A @ 230 V, 50 Hz
- Weight : 3.4 lb (1.6 kg)
- Size : 8.8 x 2.25 x 7.8 in (223 x 57 x 198 mm)
- Approvals : CE
- Optional Controllers : IRC-6, D-Fi USB

WHAT'S INCLUDED

- Power cord
- Warranty card