

SlimBANK UV-18

HIGHLIGHTS

- High-output ultraviolet LED fixture
- Direct light where it's needed using the included and removable barn doors
- Achieve smooth LED fading with built-in dimming curves
- Ideal for sound-sensitive environments due to the radiant cooling design
- Save time running extension cords by power linking multiple units
- Easily transports in the CHS-40 VIP Gear Bag
- Combine multiple units using the CBB-6 mounting bracket

SPECIFICATIONS

- DMX Channels : 2 or 5
- DMX Connectors : 3-pin XLR
- Light Source : 18 LEDs (UV) 1 W (350 mA), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Coverage Angle : 65°
- Power Linking : 22 units @ 120 V; 39 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 42 W, 0.4 A @ 120 V, 60 Hz
46 W, 0.2 A @ 230 V, 50 Hz
- Weight : 7.4 lb (3.4 kg)
- Size : 15.3 x 7.7 x 7.4 in (389 x 197 x 187 mm)
- Approvals : CE
- Wavelength : 400 to 410 nm

WHAT'S INCLUDED

- Barn doors
- Power cord
- Hanging bracket with mounting hardware
- Warranty card

