

SlimPAR 56 IRC IP

HIGHLIGHTS

- Outdoor-rated, LED wash light designed for any temporary outdoor event
- Eliminate the worry of rain or spilled drinks with innovative, weather-proof housing
- Easy to store and transport due to its lightweight, slim design
- For wireless, non-DMX control, use the optional IRC-6 remote
- Reduce the need for extra extension cords with power and data linking outputs
- Easily transport up to 4 units in the optional CHS-SP4 VIP Gear Bag
- Create coordinated light shows by linking other fixtures in the SlimPAR™ series via Master/Slave mode
- Fits best in the CHS-SP4 VIP Gear Bag
- Compact design easily fits inside sticks of TRUSST®



SPECIFICATIONS

- DMX Channels : 3 or 7
- DMX Connectors : 3-pin XLR
- Light Source : 108 LEDs (36 red, 36 green, 36 blue) 0.25 W (20 mA), 100,000 hours life expectancy
- PWM Frequency : 1,200 Hz
- Beam Angle : 14°
- Field Angle : 23°
- Illuminance : 876 lux @ 2 m
- IP Rating : IP65
- Power Linking : 49 units @ 120 V; 80 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 19 W, 0.2 A @ 120 V, 60 Hz
21 W, 0.1 A @ 230 V, 50 Hz
- Weight : 4.1 lb (1.9 kg)
- Size : 9.3 x 8 x 3.2 in (236 x 203 x 82 mm)
- Approvals : CE, MET
- Optional Controllers : IRC-6
- Startup Temperature : -4 °F to 113 °F (-20 to 45) °C
- Operating Temperature : -22 °F to 113 °F (-30 to 45) °C

WHAT'S INCLUDED

- Power Cord
- DMX (in) adaptor
- DMX (out) adaptor
- Quick Reference Guide
- Warranty card