

# SlimPAR 64 RGBA

## HIGHLIGHTS

- Generate a magnitude of colors and achieve natural color temperatures with punchy amber LEDs
- Low-profile fixture fits most places other lights cannot
- Ideal for quiet applications due to silent operation and no moving parts
- Easily create any color without DMX using the built-in digital display
- Save time running cables and extension cords by power linking multiple units
- Create coordinated light shows by linking other quad-color SlimPAR™ fixtures in Master/Slave mode
- Easily transports in the optional CHS-25 VIP Gear Bag
- Compact design easily fits inside sticks of TRUSST®



## SPECIFICATIONS

- DMX Channels : 4 or 8
- DMX Connectors : 3-pin XLR
- Light Source : 180 LEDs (39 red, 39 green, 51 blue, 51 amber) 0.25 W (20 mA), 100,000 hours life expectancy
- PWM Frequency : 1,200 Hz
- Beam Angle : 14°
- Field Angle : 23°
- Illuminance : 1,325 lux @ 2 m
- Power Linking : 40 units @ 120 V; 60 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 30 W, 0.3 A @ 120 V, 60 Hz  
33 W, 0.2 A @ 230 V, 50 Hz
- Weight : 2.8 lb (1.3 kg)
- Size : 10.8 x 10.8 x 2.6 in (276 x 275 x 66 mm)
- Approvals : CE, MET

## WHAT'S INCLUDED

- External power cord
- Quick Reference Guide