

SlimPAR H6 USB

HIGHLIGHTS

- Low-profile LED PAR with 6-in-1 LED technology (RGBAW+UV)
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with 6-in-1 LED technology
- Point-and-shoot operation of static colors and automated programs with the optional IRC-6 remote
- Save time running cables and extension cords by power linking multiple units
- Multiple control options include DMX, Master/Slave and Sound-Active modes
- Create customized colors using the built-in LED display
- Achieve smooth LED fading with built-in dimming curves
- Flicker-free operation suitable for on-camera use
- Easily transports in the optional CHS-30 VIP Gear Bag
- Sleek and lightweight to easily fit inside sticks of TRUSST®



SPECIFICATIONS

- DMX Channels : 6, 8 or 12
- DMX Connectors : 3-pin XLR
- Light Source : 6 LEDs (hex-color RGBAW+UV) 10 W (2.4 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 18 Hz
- PWM Frequency : 1.2 kHz
- Beam Angle : 23°
- Field Angle : 41°
- Illuminance : 747 lux @ 2 m
- Power Linking : 20 units @ 120 V; 39 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 25 W, 0.4 A @ 120 V, 60 Hz
23 W, 0.2 A @ 230 V, 50 Hz
- Weight : 3.4 lb (1.6 kg)
- Size : 8.3 x 3.6 x 9.6 in (211 x 91.5 x 244 mm)
- Approvals : CE
- Optional Controllers : IRC-6, D-Fi USB

WHAT'S INCLUDED

- Power cord
- Warranty card
- Quick Reference Guide
- User Manual