SlimPAR Pro Q IP

HIGHLIGHTS

- Outdoor-rated, quad-color LED wash light designed for any temporary outdoor event
- Weatherproof fixture perfect for outdoor parties or behind wet bars
- Innovative, touch-sensitive digital display
- Eliminate internal humidity and pressure with the integrated GORE valve
- Reduce the need for extra extension cords with power and data linking outputs
- Robust housing repels water, snow, dirt and sand for all-weather applications
- Flicker-free operation suitable for on-camera use
- Provides smooth and even coverage while nearly eliminating multicolored shadows
- Fits best in the CHS-40 VIP gear bag

SPECIFICATIONS

- DMX Channels : 4, 5 or 10
- DMX Connectors : 3-pin XLR
- Light Source : 12 LEDs (quad-color RGBA, (1.91A), 6W 50,000 hours life expectancy.
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 19°
- Field Angle : 33°
- Illuminance : Illuminance: 4,197 lux @ 2 m / 672 lux @ 5m
- Lumens : 2214
- IP Rating : IP65
- Power Linking : 10 units @ 120 V; 18 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Weight : 7.8 lb (3.53 kg)
- Size : 10.4 x 4.6 x 11.2 in (263 x 118 x 284 mm)
- Approvals : CE, MET
- Startup Temperature: : -4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature: : -22 °F to 113 °F (-30 °C to 45 °C)
- Cable Length: : 5 ft (1.5 m)
- Input Voltage: : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: : 75 W, 0.59 A @ 230 V, 50 Hz (EU)
- Power and Current: : 76 W, 1.02 A @ 120 V, 60 Hz (US)
- Breaker Size : 3.15 A, 250 V

WHAT'S INCLUDED

- SlimPAR Pro Q IP
- Power cord
- Quick Reference Guide



