

SlimPAR Pro W USB

HIGHLIGHTS

- Low-profile, variable white LED Par designed for any application in need of adjustable color temperatures featuring tri-color (cool white, warm white, and amber) LEDs
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- powerCON®-compatible power input/output connections for power linking
- Compatible with most 7.5" Barndoors for added light control
- Suitable for every event with either black or white housing
- Match existing lighting or tune to the perfect temperature for video using variable color temperature
- Ideal for quiet applications due to silent operation and no moving parts
- Flicker-free operation suitable for on-camera use
- Achieve smooth LED fading with built-in dimming curves that simulate halogen filaments
- Easily control static colors and automated programs with the optional IRC-6 remote
- Save time running cables and extension cords by power linking multiple units
- Trigger eye-catching effects with built-in automated programs via Master/Slave or DMX mode
- Fits best in the CHS-30 VIP Gear Bag



SPECIFICATIONS

- DMX Channels : 3, 4 or 9
- DMX Connectors : 3-pin XLR
- Light Source : 12 (tri-color CW, WW, A) 6 W (1.4 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 31 Hz
- PWM Frequency : 1.2 kHz
- Beam Angle : 17°
- Field Angle : 33°
- Illuminance : 3,097 lux @ 2 m, 592 lux @ 5 m
- Power Linking : 9 units @ 120 V; 17 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 59 W, 0.9 A @ 120 V, 60 Hz
58 W, 0.5 A @ 230 V, 50 Hz
- Weight : 7 lb (3.2 kg)
- Size : 10 x 3.9 x 11.4 in (253 x 98 x 290 mm)
- Approvals : CE, MET
- Optional Controllers : IRC-6, D-Fi USB
- CRI : 79

WHAT'S INCLUDED

- Power cord
- Gel Frame
- Gel Frame Holder
- Warranty card
- Quick Reference Guide