

# SlimPAR QUAD 3 IRC

## HIGHLIGHTS

- Low-profile, quad-color (RGBA) LED PAR with built-in infrared remote control capability
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with punchy amber LEDs
- Easy point-and-shoot operation of static colors and automated programs
- Create any color without DMX by using the built-in digital display
- Save time running cables and extension cords by power linking multiple units
- Create coordinated light shows by linking other quad-color LED SlimPAR™ fixtures in Master/Slave mode
- Perfect for quiet applications due to silent operation and no moving parts
- Safe and secure transport using the optional CHS-30 VIP Gear Bag
- Compact and lightweight to easily fit inside sticks of TRUSST®



## SPECIFICATIONS

- DMX Channels : 4 or 9
- DMX Connectors : 3-pin XLR
- Light Source : 3 LEDs (quad-color RGBA) 5 W (2 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 17 Hz
- PWM Frequency : 1,200 Hz
- Beam Angle : 20°
- Field Angle : 34°
- Illuminance : 1,065 lux @ 2 m
- Power Linking : 21 units @ 120 V; 39 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 44 W, 0.4 A @ 120 V, 60 Hz  
46 W, 0.2 A @ 230 V, 50 Hz
- Weight : 3.6 lb (1.7 kg)
- Size : 8.3 x 7.4 x 4.3 in (210 x 187 x 108 mm)
- Approvals : CE
- Optional Controllers : IRC-6

## WHAT'S INCLUDED

- Power cord
- Hanging bracket with mounting hardware
- Warranty card
- Quick Reference Guide