

Vivid Drive 28N

HIGHLIGHTS

- Video driver with numerous input/output options for any Novastar video panel
- Powerful standalone mapping without the need for a computer
- Built-in video scaler allows for quick resizing of all video content
- Buttons are backlit for easy viewing in dark environments
- Front knob can be set to control the master dimmer
- Seamlessly transition between different inputs with multiple transition effects
- Compact 1U packing eases transportation and integration into your existing setup

SPECIFICATIONS

- Rackmount : 1U
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 42 W, 0.7 A @ 120 V, 60 Hz
42 W, 0.4 A @ 230 V, 50 Hz
- Weight : 4.8 lb (2.2 kg)
- Dimensions : 19 x 12 x 1.7 in (483 x 305 x 44 mm)
- Approvals : CE
- Control Protocol : Novastar
- Control Input Connectors : USB, RJ45
- Video Input Connectors : HDMI, Display Port, DVI, VGA (x3), CVBS (x2)
- Video Output Connector : DVI, VGA, RJ45 (x2)
- Max. Supported LEDs : 1,310,720
- Max. Supported Panels (Vivid 4) : 30 per RJ45
- Max. Supported Resolution : 1920 x 1080

WHAT'S INCLUDED

- Vivid Drive 28N
- Power cord
- DVI cable
- VGA cable
- DP cable
- HDMI cable
- RJ45 cable
- DP to HDMI adaptor
- USB cable

